PSE60BT-2.5G

60W, PoE++,10/100/1000/2500Mbps Single Port PoE Active Injector



Features:

- IEEE802.3af/at/bt Compliant
- PoE Pin:1,2+/3,6-;4,5+/7,8-
- Power:60 Watts
- Input Voltage: 100~240VAC
- Output Voltage: 54VDC~57VDC
- Support 10/100/1000/2500Mbps
- PoE data & power transmission distance 100meter
- Full Over-Voltage and Over-Current Protection;
- Compact size
- Metel housing

Mechanical Characteristics:

- Length: 172.0mm(6.77inch)
- Width:76.0mm(2.99inch)
- Height:44.0mm(1.73inch)
- Weight:660g(23.28oz) per set including packings&accessories

Output Specifications:

Model	Data speed	DC output voltage	Load		Regulation	
			Min.	Max.	Line	Load
PSE60BT-2.5G	10/100/1000/2500Mbps	54V~57V	10mA	1.2A	54V~57V	

Applications:

- IP Telephones
- Wireless Access Points
- Bluetooth Access Points
- Security Cameras
- IP Point Servers
- WiMAX Access Points

Dimensional Diagram: (Unit: mm)





Data/IN interface
Data+Power output interface



AC Power input interface

Wiring Diagram:

